





## The NSB RED Battery® delivers long life for reliable and unreliable grid conditions.

- Pure lead AGM technology delivers long float life for telecom applications even at elevated temperatures
- 15 year float life at 20 °C (68°F)
- EUROBAT design life definition: Very Long Life (12+ years)
- High energy density
- Operating temperature range: -40°C to +65°C (-40°F to 149°F)
- State-of-the-art automated manufacturing ensures consistency and reliability

- Advanced 3 stage terminal design to ensure leak-free operation female M8 brass terminals provide maximum performance
- 2 year shelf life at 25 °C (77°F)
- High modulus Polyphenylene Oxide (PPO) plastic materials designed to withstand extended elevated operating temperatures and maintain high battery compression essential for reliable operation
- Non-halogenated, thermally sealed plastic casing
- Flame retardant (UL 94 VO) and LOI of at least 28%
- Integral handles and front access terminals ensure ease of installation and maintenance
- Approved as non-hazardous cargo for ground, sea, and air transport DOT 49CFR173.159(d), (i) and (ii)




## NSB 210FT RED Technical Specifications

## Dimensions (Nominal)

Height	12.9 in	Width		4.96 in
Length	22 in	Weight		132 lbs
Electrical				
Terminal			Female M8 x 1.25	
Terminal torque			8.0 Nm (71 in-lbs)	
1 hr capacity to 1.70VPC @ 20/25°C (68/77°F)			142 / 148 Ah	
3 hr capacity to 1.75VPC @ 20/25°C (68/77°F)			177 / 182 Ah	
8 hr capacity to 1.75VPC @ 20/25°C (68/77°F)			200 / 204 Ah	
10 hr capacity to 1.80VPC @ 20/25°C (68/77°F)			204 / 207 Ah	
Float voltage @ 20/25°C (68/77°F)			2.28 / 2.27 VPC	
Impedance (1Khz)			2.8 m <b>Ω</b> @ 25°C (77°F)	
Conductance			1920 S	
Short circuit current			5400 A	
Operation temperature range			-40°C to +65°C (-40°F to 149°F)	
Nominal voltage			12 V	

## **Technical Drawing**



EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605, USA Tel: +1-610-208-1991/+1-800-538-3627 NorthStar Battery Company 4000 Continental way, Springfield, MO, 65803, USA Tel: +1-417-575-8200 All NorthStar batteries are compliant with: Telcordia SR4228, IEC 60896; Bellcore GR-63-Core, Issue 1; British, German, and Russian telecom standards; UL approved and UN2800 certified. NorthStar is registered to ISO 9001 and ISO 14001.